

# REACTION TO FIRE CLASSIFICATION REPORT N° 2023/207-2

According to EN 13501-1 (2018)

(English version of classification report N°2023/207-1)

Notification by the French Government to the European Commission under n° NB 2401
Regulation (UE) n° 305/2011

Sponsor:

ONEFLOR EUROPE BV

Wittestraat 10 B 8501 HEULE BELGIUM

Product name:

WORKSHOP 55 SOLIDE / SOLIDE CLICK 55 /

RIGID 55

Description:

Polyvinyl chloride floor coverings (EN ISO 10582 family)

(see detailed description in paragraph 2)

Date of issue:

11/07/2023

The indicated classification does not prejudge the conformity of marketed materials with the samples submitted to the tests and under no circumstances, this document should not be considered as type approval or certification of the product in the sense of the L 115-27 article of the consumption's code of the law.

The reproduction of this classification report is only authorised in its integral form. It comprises 3 pages

## 1. Introduction

This classification report defines the classification assigned to the above-mentioned product in accordance with the procedures given in the NF EN 13501-1 standard (2018).

Page 2/3

## 2. Details of classified product

#### 2.1. Product standard

NF EN 14041 (2005): "Resilient, textile and laminate floor coverings - Essential characteristics".

# 2.2. Product description

Heterogeneous polyvinyl chloride floorcovering in size LVT of 1210 mm  $\times$  180 mm (EN ISO 10582 family).

Tested loose laid over a wood panel particle board without flame retarded classified  $C_{fl}$ -s1 with a density (680 ± 50) kg/m<sup>3</sup> and thickness (20 ± 2) mm.

Use surface: PVC

Type of backing: IXPE foam

Nominal mass per unit area: 10000 g/m<sup>2</sup> Nominal total thickness: 6,00 mm Nominal total wear layer: 0,55 mm

# 3. Test reports and tests results in support of this classification

#### 3.1. Tests reports

| Name of laboratory | Name of sponsor  | Test report N° | Test method                                 |
|--------------------|--|----------------|---|
| C.R.E.T.           | ONEFLOR EUROPE BV<br>Wittestraat 10<br>B 8501 HEULE<br>BELGIUM | RL 2023/509-1  | NF EN ISO 9239-1<br>(EN ISO 9239-1: 2010)   |
|                    |  | RL 2023/509-2  | NF EN ISO 11925-2<br>(EN ISO 11925-2: 2020) |

#### 3.2. Tests results

|                              |                               |                    | Results                      |                              |
|------------------------------|-------------------------------|--------------------|------------------------------|------------------------------|
| Test method                  | Product                       | Number<br>of tests | Parameters                   | Complianc<br>e<br>parameters |
| NF EN ISO 11925-2            | WORKSHOP 55 SOLIDE /          |                    | Fs ≤ 150 mm                  | Compliant                    |
| Surface exposure-15 secondes | SOLIDE CLICK 55 /<br>RIGID 55 | 6                  | Ignition of the filter paper | Compliant                    |

| y  |         |                            |                 | Results                           |
|--|---------|----------------------------|-----------------|-----------------------------------|
| Test method  | Product | Number of tests            | Parameters      | Continuous parameters: mean value |
| NF EN ISO 9239-1 WORKSHOP 55 SOLIDE /<br>SOLIDE CLICK 55 /<br>RIGID 55 | 3       | Critical heat flux (kW/m²) | ≥ 11            |                                   |
|  |         | 3                          | Smoke (% X min) | 66,6                              |

# 4. Classification and field of application

#### 4.1. Reference of classification

This classification has been carried out in accordance with EN 13501-1 (2018).

#### 4.2. Classification

| Fire behaviour             |   | Smoke production |
|----------------------------|---|------------------|
| $\mathrm{B}_{\mathrm{fl}}$ | - | s1               |

Classification: B<sub>fl</sub>-s1

## 4.3. Field of application

This classification is valid for the following end use applications:

Loose laid over a wood panel particle board without flame retarded classified  $C_{fl}$ -s1 with a density  $\geq 510 \text{ kg/m}^3$  and over a fibre-cement  $A1_{fl}$  or  $A2_{fl}$  class with a density  $\geq 1350 \text{ kg/m}^3$ .

This classification is valid for the following product parameters:

A nominal mass per unit area of: 10000 g/m²

• A nominal thickness of: 6,00 mm

A nominal thickness wear layer: 0,55 mm

#### 5. Limitations

This classification document does not represent type approval or certification of the product.

"The classification assigned to the product in this report is appropriate to a declaration of conformity by the manufacturer within the context of system 3 of AVCP and CE marking under the Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of constructions products.

The manufacturer has made a declaration, which is held on file. This confirms that the products design requires no specific processes, procedures or stages (no addition of flame-retardants, limitation of organic content, or addition of fillers) that are aimed at enhancing the fire performance in order to obtain the classification achieved. As a consequence the manufacturer has concluded that system 3 attestation is appropriate.

The test laboratory has, therefore, played no part in sampling the product for the test, although it holds appropriate references, supplied by the manufacturer, to provide for traceability of the samples tested."

For the SARL C.R.E.T. The Technical Director Marc WELCOMME

End of the classification report